

# RT125



SPECIFICATIONS	RT125
TYPE OF VEHICLE (4x4)	Commercial Equipment (ex. Toro RT600 Riding Trencher)
RECOMMENDED MAX GVW	12,500 lbs
RECOMMENDED MAX SPEED	20 mph
FRAME CONSTRUCTION	Steel
STEERING ASSIST (ADDS 25 LBS)	N/A
ASSEMBLY WEIGHT	415
INTERNAL SUSPENSION	Concentric Pivot w/ Independent Rubber Torsion Rockers
TRACK TREAD WIDTH	15"
TRACK TREAD STYLE	All-Terrian, Self-Cleaning XTHD
TRACK MATERIAL	Rubber with Internal Composite Rods/Cord
RECOMMENDED OPERATING TEMP	(Ambient) -40°F to +130°F
AXLE HEIGHT	18.7"
GROUND CONTACT LENGTH	(Hard Surface) 28.9" / (Soft Surface) 42.3"
GROUND CONTACT SURFACE AREA	434 sq in min / 635 sq in max
SPROCKET DIAMETER (STANDARD)	18"
WHEEL TYPE	(4) 10" x 2.5" and (4) 8" x 2.5" HD Extra Seals
WHEEL COUNT	8, 2 rows
WHEEL MATERIAL	UMHW / Rubber
PAINT COLOR	Silver Metallic (Standard, other colors available)
	<b>* ALL SPECS ARE PER CORNER</b>



TORO RT600 RIDING TRENCHER

