RT80



SPECIFICATIONS	RT80
TYPE OF VEHICLE (4x4)	Mini Loader, Trenchers, Compact Equipment
RECOMMENDED MAX GVW	8,000 lbs
FRAME CONSTRUCTION	Steel
STEERING ASSIST (ADDS 25 LBS)	N/A
ASSEMBLY WEIGHT	180 lbs
INTERNAL SUSPENSION	Rubber Torsion
TRACK TREAD WIDTH	15"
TRACK TREAD STYLE	All-Terrian, Self-Cleaning
TRACK MATERIAL	Rubber with Internal Composite Cord
RECOMMENDED OPERATING TEMP	(Ambient) -40°F to +130°F
AXLE HEIGHT	19.2"
GROUND CONTACT LENGTH	(Hard Surface) 18.5" / (Soft Surface) 33.3"
GROUND CONTACT SURFACE AREA	277 sq in min / 500 sq in max
SPROCKET DIAMETER (STANDARD)	17.3"
WHEEL TYPE	(4) 12" x 1.5" and (2) 6" x 1.5" HD Extra Seals
WHEEL COUNT	3, 2 rows
WHEEL MATERIAL	UMHW / Rubber
PAINT COLOR	Graphite Gray (Standard, other colors available)
	* ALL SPECS ARE PER CORNER





